



SAWN LONGITUDINAL JOINT FOR CRCP OR CRCB
(CONSTRUCTED IN MORE THAN ONE LANE WIDTH IN ONE OPERATION)

NOTES:-

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE STATED.
2. TIE BARS SHALL BE PLACED ABOUT THE JOINT ± 50 AT THE SAME SPACINGS AS AND ADJACENT TO THE TRANSVERSE REINFORCEMENT PROTECTIVE COATING TO BE APPLIED TO THE CENTRE 150 (MIN) OF TIE BARS.
3. REINFORCEMENT SHALL CONFORM TO CC-SPW-01000.

TIE BARS		
DIA.	LENGTH L	GRADE
12	750	B500B OR B500C
16	600	B500B OR B500C
20	500	B500B OR B500C



PUBLICATION TITLE

**CONCRETE PAVEMENTS
LONGITUDINAL JOINT (CONTINUOUSLY REINFORCED CONCRETE PAVEMENT OR BASE)**

STREAM

STANDARD CONSTRUCTION DETAILS (SCD)

HISTORICAL REFERENCE

RCD/1000/24

DOCUMENTATION SET

STANDARD

PUBLICATION DATE

DECEMBER 2010

PUBLICATION NUMBER

ACTIVITY

CC

STREAM

SCD

DRAWING NUMBER

01024