



LONGITUDINAL DUCTS

NOTES :-

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. SEE DN-GEO-03036 FOR DIMENSIONS OF CROSS-SECTION ELEMENTS.
3. FOR DETAILS OF ROAD MARKINGS SEE THE TRAFFIC SIGNS MANUAL.
4. FOR LANE WIDTHS OF CLIMBING LANE SECTIONS ON TYPE 3 SINGLE CARRIAGEWAY SEE DN-GEO-03031.
5. THE VERGE WIDTH SHOULD BE INCREASED AS REQUIRED TO ACCOMMODATE THE FEATURES AND SERVICES CONTAINED THEREIN.
6. THE VERGE WIDTH SHOULD BE INCREASED AS NECESSARY TO ACCOMMODATE MANDATORY PEDESTRIAN/CYCLIST FACILITIES.
7. TWO WAY CYCLE FACILITIES SHOULD BE PROVIDED ON ONE SIDE OF THE ROAD UNLESS SITE SPECIFIC CONDITIONS REQUIRE FACILITIES ON BOTH SIDES.
8. LONGITUDINAL DUCTS ARE TO BE PROVIDED WITHIN A VERGE; REFER TO DN-ITS-03029 FOR GUIDANCE ON THE PROVISION OF LONGITUDINAL COMMUNICATION DUCTS. REFER TO CC-SPW-00500 AND CC-SPW-01500 FOR FURTHER DETAILS ON DUCT SPECIFICATION.



PUBLICATION TITLE

ROAD TYPE AND CROSS-SECTION
TYPE 3 SINGLE CARRIAGEWAY

ACTIVITY

STREAM

STANDARD CONSTRUCTION DETAILS (SCD)

HISTORICAL REFERENCE

RCD/000/3

DOCUMENTATION SET

STANDARDS

PUBLICATION DATE

DECEMBER 2017

PUBLICATION NUMBER

ACTIVITY

CC

STREAM

SCD

DRAWING NUMBER

00003