



NOTES :-

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. SEE DN-GEO-03036 FOR DIMENSIONS OF CROSS-SECTION ELEMENTS.
3. FOR DETAILS OF ROAD MARKINGS SEE THE TRAFFIC SIGNS MANUAL.
4. WIDTH OF CENTRAL RESERVE FOR A DUAL CARRIAGEWAY MOTORWAY IS DETERMINED BY THE TYPE OF SAFETY FENCE OR BARRIER. REFER TO DN-REQ-03034.
5. THE VERGE WIDTH SHOULD BE INCREASED AS REQUIRED TO ACCOMMODATE THE FEATURES AND SERVICES CONTAINED THEREIN.

6. LONGITUDINAL DUCTS ARE TO BE PROVIDED WITH IN EACH VERGE, REFER TO DN-ITS-03029 FOR THE MINIMUM REQUIREMENTS FOR PROVISION OF LONGITUDINAL COMMUNICATION DUCTS. REFER TO CC-SPW-00500 AND CC-SPW-01500 FOR FURTHER DETAILS ON DUCT SPECIFICATION.
7. WHERE THE TRAFFIC ASSESMENT INDICATES MORE THAN TWO LANES ARE REQUIRED IN EACH DIRECTION, ANY ADDITIONAL LANES SHALL BE 3.5M IN WIDTH. DETAILS OF VERGES, HARD SHOULDERS AND THE CENTRAL RESERVE SHALL BE THE SAME AS FOR 2 LANES IN EACH DIRECTION.

 <p>Bonneagar Iompair Éireann Transport Infrastructure Ireland</p>	 <p>Construction &amp; Commissioning</p>	<p>PUBLICATION TITLE</p> <p>ROAD TYPE AND CROSS-SECTION STANDARD DUAL CARRIAGEWAY MOTORWAY (RURAL AND URBAN)</p>								
	<p>ACTIVITY</p> <p>STANDARD CONSTRUCTION DETAILS (SCD)</p>	<p>HISTORICAL REFERENCE</p> <p>RCD/000/7</p>	<p>DOCUMENTATION SET</p> <p>STANDARDS</p>	<p>PUBLICATION DATE</p> <p>JUNE 2017</p>	<p>PUBLICATION NUMBER</p> <table border="1"> <tr> <td>ACTIVITY</td> <td>STREAM</td> <td>DRAWING NUMBER</td> </tr> <tr> <td>CC</td> <td>SCD</td> <td>00007</td> </tr> </table>	ACTIVITY	STREAM	DRAWING NUMBER	CC	SCD
ACTIVITY	STREAM	DRAWING NUMBER								
CC	SCD	00007								