



NOTES :-

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. SEE DN-GEO-03036 FOR DIMENSIONS OF CROSS-SECTION ELEMENTS.
3. FOR DETAILS OF ROAD MARKINGS SEE THE TRAFFIC SIGNS MANUAL.
4. THE VERGE WIDTH SHOULD BE INCREASED AS REQUIRED TO ACCOMMODATE THE FEATURES AND SERVICES CONTAINED THEREIN.
5. LONGITUDINAL DUCTS ARE TO BE PROVIDED WITH IN EACH VERGE, REFER TO DN-ITS-03029 FOR THE MINIMUM REQUIREMENTS FOR PROVISION OF LONGITUDINAL COMMUNICATION DUCTS. REFER TO CC-SPW-00500 (SERIES 500) AND CC-SPW-01500 (SERIES 1500) FOR FURTHER DETAILS ON DUCT SPECIFICATION.



PUBLICATION TITLE

ROAD TYPE AND CROSS-SECTION
SLIP ROADS, INTERCHANGE LINKS AND LOOPS: 2 LANES

STREAM

STANDARD CONSTRUCTION DETAILS (SCD)

HISTORICAL REFERENCE

RCD/000/10

DOCUMENTATION SET

STANDARDS

PUBLICATION DATE

APRIL 2014

PUBLICATION NUMBER

ACTIVITY	STREAM	DRAWING NUMBER
CC	SCD	00010