



NOTES :-

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. SEE DN-GEO-03036 FOR DIMENSIONS OF CROSS-SECTION ELEMENTS.
3. FOR DETAILS OF ROAD MARKINGS SEE THE TRAFFIC SIGNS MANUAL.
4. FOR LANE WIDTHS OF CLIMBING LANES ON ROADS SEE DN-GEO-03031.
5. THE VERGE WIDTH SHOULD BE INCREASED AS REQUIRED TO ACCOMMODATE THE FEATURES AND SERVICES CONTAINED THEREIN.
6. TABLE 6.1 OF DN-GEO-03031 DOES NOT APPLY TO URBAN ROADS.
7. FOOTPATH/ CYCLE TRACK WIDTH AS PER TABLE 3.5 OF DN-GEO-03036.
8. WHERE REQUIRED, LONGITUDINAL DUCTS ARE TO BE PROVIDED WITHIN A VERGE: REFER TO DN-ITS-03029 FOR GUIDANCE ON THE PROVISIONS OF LONGITUDINAL COMMUNICATIONS DUCTS. REFER TO CC-SPW-00500 (SERIES 500 AND CC-SPW-01500 (SERIES 1500) FOR FURTHER DETAILS ON DUCT SPECIFICATIONS.