



Notes :-

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. ROUNDING OCCURS OVER 1500mm LENGTH, 750mm EITHER SIDE OF INTERSECTION BETWEEN VERGE AND BATTER.
3. SET BACK REQUIREMENTS IN ACCORDANCE WITH DN-REQ-03034.
4. PERMITTED VERGE SIDE EDGE DRAINAGE OPTIONS ARE INDICATED IN DN-DNG-03022.
5. REFER TO CC-SCD-00510, CC-SCD-00511 AND CC-SCD-00512 FOR GULLY DETAILS.
6. REFER TO CC-SCD-00540, CC-SCD-00541 AND CC-SCD-00542 AND NARROW DRAIN DETAILS.
7. EXTENSION OF CAPPING LAYER IN ACCORDANCE WITH CC-SCD-00105 IS ACCEPTABLE IN LIEU OF FIN OR NARROW FILTER DRAIN WHERE BASE OF CAPPING CAN BE EXTENDED OF EMBANKMENT ABOVE ADJACENT GROUND LEVEL.
8. A FILTER DRAIN MAY BE REQUIRED IN LIEU OF FIN OR NARROW FILTER DRAIN WHERE THESE DO NOT HAVE SUFFICIENT CAPACITY FOR SUBSURFACE DRAINAGE.