



NOTES :

1. THE FOLLOWING IS ONE OF THE STANDARD FENCES THAT ARE SUGGESTED FOR ROAD WORKS AND THE TYPE REQUIRED, OR ANY VARIATIONS OF THESE DETAILS SHALL BE AS SHOWN ON THE DRAWINGS. FENCE TYPE IS SW120 TO B.S.1722 PART 3 AND AS SHOWN ON THIS DETAIL.
2. ALL LINE WIRE, STIRRUP WIRE AND BARBED WIRE SHALL BE ZINC COATED TO COMPLY WITH BS 443.
3. WIRE SHALL BE FIXED TO POSTS BY 40 x 4 DIA. STAPLES.
4. MESH TYPE OR BARBED WIRE WHERE REQUIRED SHALL BE SPECIFIED IN APPENDIX 3/1 TO THE SPECIFICATION.
5. POST HOLES FALLING IN ROCK TO BE EXCAVATED TO THE DEPTH SHOWN ON THIS DRAWING OR, WITH THE ENGINEER'S APPROVAL, TO A DEPTH OF 500mm, AND SHALL BE BACKFILLED WITH ST2 CONCRETE. WHERE A REDUCED DEPTH OF HOLE IS ACCEPTED BY THE ENGINEER, THE TOP OF THE POST SHALL BE SUITABLY CUT AND TREATED IN ACCORDANCE WITH THE RELEVANT CCA OR CREOSOTE MANUFACTURER'S RECOMMENDATIONS.
6. WHEN THIS TYPE OF FENCE OR VARIATIONS OF IT ARE USED FOR ACCOMMODATION WORK FENCES, THE REQUIREMENTS ARE INCLUDED IN APPENDIX 1/15 AND ON THE DRAWINGS.
7. ALL DIMENSIONS ARE IN MILLIMETRES.