

<i>Product Name</i>	
<i>Installed By</i>	
<i>L</i>	
<i>W_m</i>	
<i>ISL</i>	
<i>VRS A, L</i>	
<i>VRS B, L</i>	
<i>Install Date</i>	

Identification Label for Road Restraint System - Transition

<i>Product Name</i>	
<i>Installed By</i>	
<i>T</i>	
<i>Direction Class</i>	
<i>ISL</i>	
<i>D (X/ Y)</i>	
<i>Za/ Zd</i>	
<i>Install Date</i>	

Identification Label for Road Restraint System - Terminal

<i>Product Name</i>	
<i>Installed By</i>	
<i>T</i>	
<i>R/ Non-R</i>	
<i>ISL</i>	
<i>D</i>	
<i>Z</i>	
<i>Install Date</i>	

Identification Label for Road Restraint System - Crash Cushion

- NOTES:
- REFER TO CC-SCD-00416, IDENTIFICATION LABEL FOR ROAD RESTRAINT SYSTEM - SAFETY BARRIER
 - IDENTIFICATION LABELS SHALL BE CENTRALLY PLACED ON ANY TRANSITION, TERMINAL OR CRASH CUSHION
 - ALL IDENTIFICATION LABELS SHALL BE ROAD FACING, VISIBLE, LEGIBLE AND INDELIBLE
 - PEEL ADHESION LABEL IDENTIFICATION PROPERTIES SHALL COMPLY WITH PSTC-1, 15-MIN, RT 21°C AND ACHIEVE A MINIMUM VALUE OF 0.89KG/CM
 - OUTDOOR DURABILITY SHALL BE RATED FOR A DURATION OF 7 (SEVEN) YEARS (UNPRINTED)
 - SURFACE FINISH OF IDENTIFICATION LABELS SHALL ENSURE A TYPICAL VALUE OF 40% TO 60% BASED ON A GLOSS METER 60° REFLECTION
 - ALL DIMENSIONS SHOWN ARE IN MM
 - "INSTALLED BY" SHOULD INCLUDE THE COMPANY NAME ONLY. COMPANY LOGO/ BRANDING IS NOT PERMITTED
 - ABBREVIATIONS:
 - L - CONTAINMENT LEVEL
 - W_m - WORKING WIDTH
 - ISL - IMPACT SEVERITY LEVEL
 - Za/ Zd - EXIT BOX CLASS
 - VRS A, L - CONNECTING FROM CONTAINMENT LEVEL
 - VRS B, L - CONNECTING TO CONTAINMENT LEVEL
 - T - PERFORMANCE CLASS
 - R/ NON-R - REDIRECTIVE/ NON-REDIRECTIVE
 - D - PERMANENT LATERAL DISPLACEMENT CLASS
 - Z - REDIRECTION ZONE CLASS
 - INSTALL DATE - DATE SYSTEM INSTALLED ON SITE



ACTIVITY



STREAM

STANDARD CONSTRUCTION DETAILS (SCD)

PUBLICATION TITLE

IDENTIFICATION LABEL FOR ROAD RESTRAINT SYSTEM - TRANSITION, TERMINAL AND CRASH CUSHION

HISTORICAL REFERENCE

N/A

DOCUMENTATION SET

STANDARDS

PUBLICATION DATE

JUNE 2020

PUBLICATION NUMBER

CC SCD 00417