

## WARPING JOINT - WITH SAWN GROOVE

THE BAR DIMENSIONS		
GRADE OF STEEL	B500B OR B500C	
TIE BAR DIAMETER	12	
TIE BAR LENGTH L	750	

COVER TO TIE BARS		
SLAB THICKNESS D	≥ 200	< 200
COVER X	30	20

- NOTES:
  1. ALL DIMENSIONS ARE IN MILLIMETRES.

  2. WARPING JOINTS SHALL BE CONSTRUCTED AND SEALED IN ACCORDANCE WITH CC-SPW-01000, THE TIE BAR SPACING SHALL BE VARIED WHERE NECESSARY SO THAT NO TIE BAR IS WITHIN 150 OF A SLAB EDGE OR A JOINT PARALLEL TO THE BARS.
  3. REINFORCEMENT SHALL CONFORM TO CC-SPW-01000.





PUBLICATION TITLE

**CONCRETE PAVEMENT** WARPING JOINTS (UNREINFORCED SLABS ONLY)

HISTORICAL REFERENCE DOCUMENTATION SET PUBLICATION DATE

RCD/1000/4 **STANDARDS** 

**NOVEMBER 2010** 

ACTIVITY STREAM СС SCD

PUBLICATION NUMBER

DRAWING NUMBER 01004