



RIGID TO FLEXIBLE CONSTRUCTION (SURFACE SLABS)

NOTES:-

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE STATED.
2. AT UNDERBRIDGES THE BASE ADJACENT TO THE STRUCTURE SHALL BE 5M (MIN.).
3. THE DEPTH OF TRANSITION SLAB SHALL NOT BE LESS THAN 200. IF NECESSARY, THE THICKNESS OF THE LAST BAY OF RIGID PAVEMENT SHALL BE TAPERED TO MATCH, SO THAT THE SUB-BASE SURFACE LEVEL IS CONTINUOUS WITHOUT STEPS.
4. AT BURIED STRUCTURES THE BASE AND SUB-BASE SHALL BE CONTINUED OVER THE STRUCTURE. THE SUB-BASE SHALL BE ISOLATED FROM THE STRUCTURE BY NOT LESS THAN 150mm OF GRANULAR FILL.



PUBLICATION TITLE

**CONCRETE PAVEMENTS
TRANSITIONS FROM RIGID TO FLEXIBLE CONSTRUCTION**

ACTIVITY

STREAM

STANDARD CONSTRUCTION DETAILS (SCD)

HISTORICAL REFERENCE

RCD/1000/6

DOCUMENTATION SET

STANDARD

PUBLICATION DATE

NOVEMBER 2010

PUBLICATION NUMBER

ACTIVITY STREAM DRAWING NUMBER

CC SCD 01006