



TYPICAL METHOD OF MARKING CABLES

NOTES:

1. ALL CABLES SHALL BE CLEARLY AND UNAMBIGUOUSLY MARKED TO SHOW DETAILS OF CABLE ROUTES AND DESTINATIONS.
2. AT CABLE JOINT ENCLOSURES (CJE) THE CABLE SHALL BE MARKED IMMEDIATELY ADJACENT TO THE CJE OVER THE HEAT SHRINK MATERIAL.
3. THE ROAD AUTHORITY SHALL BE CONSULTED TO AGREE UPON CABLE MARKER LETTERS AND/OR NUMERALS TO BE FITTED BY THE CABLING CONTRACTOR.
4. EACH END OF EVERY CABLE SHALL FITTED WITH AN IDENTIFICATION TAG ADJACENT TO THE CABLE GLAND SHROUD.
5. IDENTIFICATION TAG TEXT SHALL BE INDELIBLE AND SHALL BE FASTENED SECURELY USING CABLE TIES. HAND WRITTEN, SELF-ADHESIVE PLASTIC LABELS SHALL NOT BE ACCEPTED AS A PERMANENT MEANS OF IDENTIFICATION.

NOT TO SCALE

TII PUBLICATION NUMBER: CC-SCD-01519

P2	06/15
P1	10/13
Issue	Date