



NOTES:

1. ALL DIMENSIONS ARE IN METRES.
2. ALL LOOPS TO BE 3 TURNS.
3. LOOP TAILS TO BE IDENTIFIED WITH LOOP REFERENCE SHOWN USING PREPRINTED DURABLE PLASTIC SLEEVE.
4. THIS IS A GENERAL DRAWING. LOOP WIDTHS WILL VARY ACCORDING TO LANE WIDTHS.
5. CONSULT WITH DETECTOR MANUFACTURER ON FREQUENCY OF CHANNEL ALLOCATION.
6. SINGLE PAIR ARMoured FEEDER CABLE IS REQUIRED FOR SPEED LOOPS IN EACH LANE.
7. TOLERANCE ± 0.02 METRES UNLESS OTHERWISE STATED.
8. DETAILS X1, X2 AND X3 ARE SHOWN ON DRAWING RCD/1500/027.
9. LOOP SLOT TYPES S1 TO S3 ARE SHOWN ON DRAWING RCD/1500/025.
9. FOR THE INSTALLATION OF DETECTOR LOOPS ON MOTORWAYS AND NATIONAL ROADS REFER TO DMRB HD 20.

NOT TO SCALE

TII PUBLICATION NUMBER: CC-SCD-01536

	ROAD CONSTRUCTION DETAILS	INSTALLATION DRAWING TCC			DETECTOR LOOP LAYOUT – SHEET 4	Drawing No.
			P1	10/13		RCD/
			Issue	Date		1500/036