



SPEED MEASURING LOOPS

NOTES:

1. ALL DIMENSIONS ARE IN METRES.
2. ALL LOOPS TO BE 3 TURNS.
3. C OF C INDICATES CENTRE OF CARRIAGEWAY.
4. REFER TO DETECTOR MANUFACTURER FOR MAXIMUM FEEDER LENGTH.
5. SEE DRAWING RCS/1500/029 FOR DETAIL OF CROSS-CUT OF CORNERS OF LOOP SLOT.
6. FEEDER CABLE 1 CONNECTED TO LOOPS IN LEFT HAND LANE. FEEDER CABLE 2 CONNECTED TO LOOPS IN RIGHT HAND LANE.
7. DISTANCE FROM STOP LINES ARE CONTAINED IN UK HA MCE 0108 SITING OF INDUCTIVE LOOPS FOR VEHICLE DETECTING EQUIPMENTS AT PERMANENT ROAD TRAFFIC SIGNAL INSTALLATION SPECIFICATION.
8. FOR THE INSTALLATION OF DETECTOR LOOPS ON MOTORWAYS AND NATIONAL ROADS REFER TO DMRB HD 20.

TII PUBLICATION NUMBER: CC-SCD-01544

NOT TO SCALE



ROAD CONSTRUCTION  
DETAILS

INSTALLATION  
DRAWING TCC

P1	10/13
Issue	Date

LOOP (INDUCTIVE) ALL-PURPOSE ROAD  
SPEED MEASURING LOOPS – SHEET 2

Drawing No.  
RCD/  
1500/044

Created using CADalot http://www.cadsoft.com/cadsoft/