



- NOTES:-
1. ALL DIMENSIONS ARE IN MILLIMETERS.
  2. CATTLE GRIDS SHALL COMPLY WITH THIS DETAIL AND THE ADDITIONAL REQUIREMENTS OF I.S. 185 OR BS 4008.
  3. THE PIT LENGTH FOR STOCK EXCEPT DEER SHALL BE AT LEAST 2.6m. FOR DEER THIS SHALL BE INCREASED TO AT LEAST 4.0m.
  4. THE PIT WIDTH SHALL BE EQUAL TO THE WIDTH OF THE ACCESS ON WHICH IT IS BEING PROVIDED BUT SHALL NOT BE LESS THAN 2.75m.
  5. THE PIT DEPTH SHALL BE AT LEAST 250mm WHICH IS CONSIDERED THE PREFERRED DEPTH IN TERMS OF ANIMAL WELFARE. ANY INCREASED DEPTH SHOULD BE ONLY TO PERMIT DRAINAGE FALLS AND/OR TO ACCOMMODATE STRUCTURAL MEMBERS.
  6. ADEQUATE DRAINAGE SHALL BE PROVIDED TO PREVENT WATER COLLECTING IN THE PIT.
  7. GUARD FENCING SHALL BE PROVIDED WHERE SPECIFIED TO PREVENT ANIMALS SCRAMBLING ROUND THE TERMINAL POST OR PILLARS OF THE FENCE OR WALL THAT MEETS THE GRID ON EACH SIDE.
  8. RAMPS TO AID THE ESCAPE OF SMALL ANIMALS SHALL BE PROVIDED IN ONE OR TWO CORNERS TO EXIT THE PIT ON THE SIDE AWAY FROM THE STOCK CONTAINMENT.