



NOTES:

1. A CLEAR FOOTPATH PASSAGE WIDTH OF 1.2m SHOULD BE MAINTAINED BETWEEN ALL STREET FURNITURE, TREES ETC.
2. FOR TACTILE PAVING DETAILS REFER TO CC-SCD-05027; FOR POLE DETAILS REFER TO CC-SCD-05027 AND CC-SCD-05033.
3. FOR DETAILS OF THE LENGTH OF ZIGZAG MARKINGS REFER TO THE TRAFFIC SIGNS MANUAL.
4. THIS LAYOUT CAN ALSO BE USED FOR A TOUCAN CROSSING BUT WITH A CROSSING WALKWAY WIDTH OF 4m TO 5m.
5. DROPPED KERBS MUST BE LAID FLUSH WITH CARRIAGEWAY SURFACE, WITH AN ABSOLUTE MAXIMUM UPSTAND OF 6mm.
6. SEE CC-SCD-05027 FOR KEY TO SYMBOLS.

KEY

 RED TACTILE BLISTER PAVING (400mm x 400mm)



ACTIVITY



PUBLICATION TITLE

PUFFIN CROSSING ZIG ZAG ROAD MARKINGS AND GENERAL LAYOUT

STREAM

STANDARD CONSTRUCTION DETAILS (SCD)

HISTORICAL REFERENCE

PCS 005

DOCUMENTATION SET

STANDARDS

PUBLICATION DATE

AUGUST 2018

PUBLICATION NUMBER

CC SCD 05025