



NOTES:

1. A CLEAR FOOTPATH PASSAGE WIDTH OF 1.2m SHOULD BE MAINTAINED BETWEEN ALL STREET FURNITURE, TREES ETC.
2. FOR DETAILS OF THE REFUGE ISLAND REFER TO CC-SCD-05016. FOR TACTILE PAVING AND POLE DETAILS REFER TO CC-SCD-05027. FOR POLE DETAILS REFER TO CC-SCD-05033.
3. THIS LAYOUT CAN ALSO BE USED FOR A TOUCAN CROSSING BUT WITH A CROSSING WALKWAY WIDTH OF 4m TO 5m.
4. FOR DETAILS OF THE LENGTH OF ZIGZAG MARKINGS REFER TO THE TRAFFIC SIGNS MANUAL.
5. DROPPED KERBS MUST BE LAID FLUSH WITH CARRIAGEWAY SURFACE, WITH AN ABSOLUTE MAXIMUM UPSTAND OF 6mm.
6. SEE CC-SCD-05027 FOR KEY TO SYMBOLS.

KEY	
	RED TACTILE BLISTER PAVING (400mm x 400mm)

 Bonneagar Iompair Éireann Transport Infrastructure Ireland	 Construction & Commissioning	PUBLICATION TITLE PUFFIN CROSSING WITH REFUGE ISLAND ZIG ZAG ROAD MARKINGS AND GENERAL LAYOUT			
	STREAM STANDARD CONSTRUCTION DETAILS (SCD)	HISTORICAL REFERENCE PCS 006	DOCUMENTATION SET STANDARDS	PUBLICATION DATE AUGUST 2018	PUBLICATION NUMBER CC SCD 05026