



LEGEND:

- (A) CUT CIRCULAR HOLES FOR ROUND COVERS. FIT AS CLOSELY POSSIBLE 5-10mm JOINTS
- (B) EXISTING COVERS THAT ARE LESS THAN 5 DEGREES OUT OF ALIGNMENT SHOULD BE RESET ON THE EXISTING CHAMBER WALL
- (C) NEW UTILITY COVERS TO BE ALIGNED PARALLEL TO THE KERB. ALIGN AS MANY SIDES OF THE COVER WITH THE PAVING JOINTS AS POSSIBLE. ALIGN SMALL COVERS WITH PAVING JOINTS OR CUT A HOLE THROUGH THE PAVING
- (D) CUT PAVING AROUND THE PIT COVER AS REQUIRED, FOLLOWING THE SHAPE OF THE COVER, WITH JOINTS NO MORE THAN 5-10mm OR AS NARROW AS THE COVER LID PERMITS
- (E) WHERE GAP IS LESS THAN 50mm AN APPROVED FILL MAY BE USED IF REQUIRED. WHERE GAP IS MORE THAN 50mm A PIECE OF STONE OR SLAB CUT TO FIT, MUST BE USED



ACTIVITY	
STREAM	STANDARD CONSTRUCTION DETAILS (SCD)

PUBLICATION TITLE			
UTILITY LIDS IN PAVING DETAILS			
HISTORICAL REFERENCE	DOCUMENTATION SET	PUBLICATION DATE	PUBLICATION NUMBER
N/A	STANDARDS	JULY 2021	<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 2px;">CC</div> <div style="border: 1px solid black; padding: 2px;">SCD</div> <div style="border: 1px solid black; padding: 2px;">05143</div> </div>